

Glass Kiln Specifications 2017											
Model	TUV Listed U.S. & Canada	Chamber Width or Diameter	Chamber Length	Chamber Depth or Height	Maximum Usable Temperature	Cubic Feet	Volts	Amps	Watts	Power Receptacle	Ship Weight
Copper	120V INF – No All Other - Yes	10" (25.4cm)	9" (22.9cm)	6.5" H (15.6cm)	2200°F (1204°C)	.340 (9.6L)	120V	12A	1440W	NEMA 5-15R	54 lb. (25kg)
							240V	13A	3120W	NEMA 6-20R	
Fishbone	No	14.25" (36.2cm)	7.5" (19cm)	3.5" H (8.9cm)	1200°F (649LC)	.220 (6.2L)	120V	12A	1440W	NEMA 5-15R	45 lb. (20kg)
							230V	6.3A	1449W	NEMA 6-20R	
GT 14-6	120V INF – No All Other - Yes	14.5" (36.8cm)		6.5" (16.5cm)	1650°F (899°C)	.700 (19.8L)	120V	12A	1440W	NEMA 5-15R	70 lb. (32kg)
							230V	12.5A	2875W	NEMA 6-20R	
GTS 18-9	Yes	17.5" (44.5cm)		9" (22.9cm)	1800°F (982°C)	1.30 (36.8L)	240V	27A	6420W	NEMA 6-30R	100 lb. (46kg)
							208V	27A	5616W	NEMA 6-30R	
							400V	14.4A	6000W	Varies	
GTS 18-13	Yes	17.5" (44.5cm)		13.5" (34.3cm)	1800°F (982°C)	1.95 (55.2L)	240V	27A	6420W	NEMA 6-30R	120 lb. (55kg)
							208V	27A	5616W	NEMA 6-30R	
							400V	14.4A	6000W	Varies	
GTS 23-9	Yes	23.5" (59.7cm)		9" (22.9cm)	1800°F (982°C)	2.34 (66.3L)	240V	30A	7200W	NEMA 6-50R	140 lb. (64kg)
							208V	30A	6240W	NEMA 6-50R	
							400V	14.4A	6600W	Varies	
GTS 23-13	Yes	23.5" (59.7cm)		13.5" (34.3cm)	1800°F (982°C)	3.51 (99.4L)	240V	30A	7200W	NEMA 6-50R	195 lb. (89kg)
							208V	30A	6240W	NEMA 6-50R	
							400V	14.4A	6600W	Varies	
GTS 2541-9	Yes	41" (104.1cm)	25.5" (64.8cm)	9" (22.9cm)	1800°F (982°C)	4.80 (135.9L)	240V	40A	9600W	NEMA 6-50R	280 lb. (127kg)
							208V	45A	9360W	NEMA 6-50R	
							400V	15.7A	10,800W	Varies	
GTS 2541-13	Yes	41" (104.1cm)	25.5" (64.8cm)	13.5" (34.3cm)	1800°F (982°C)	7.20 (203.9L)	240V	40A	9600W	NEMA 6-50R	310 lb. (141kg)
							208V	45A	9360W	NEMA 6-50R	
							400V	15.7A	10,800W	Varies	
GTS 41	No	40.5" (102.9cm)	25.25" (64.1CM)	13.5" D (34.3CM)	1800°F (982°C)	7.52 (213L)	240V	45A	10800W	NEMA 6-50R	365 lb. (166kg)
							208V	48A	9984W	NEMA 6-50R	
							400V	17A	10,071W	Varies	
Hot Shot	Yes	14.5" (36.8cm)		6.5" (16.5cm)	1650°F (899°C)	.700 (19.8L)	120V	12A	1440W	NEMA 5-15R	70 lb. (32kg)
							230V	12.5A	2875W	NEMA 6-20R	
Kingpin 88	No	8" (20.3cm)	8" (20.3cm)	6" H (15.2cm)	2000°F (1093°C)	.220 (6.2L)	120V	12A	1440W	NEMA 5-15R	40 lb. (18kg)
							230V	6.3A	1449W	NEMA 6-20R	

Glass Kiln Specifications 2017											
Model	TUV Listed U.S. & Canada	Chamber Width or Diameter	Chamber Length	Chamber Depth or Height	Maximum Usable Temperature	Cubic Feet	Volts	Amps	Watts	Power Receptacle	Ship Weight
Studio Pro	No	8" (20.3cm)	8" (20.3cm)	4.5" D (11.4cm)	1800°F (982°C)	.167 (4.7L)	120V	12A	1440W	NEMA 5-15R	30 lb. (14kg)
							230V	9.6A	2208W	NEMA 6-20R	
Studio Pro STP	Yes	8" (20.3cm)	8" (20.3cm)	4.5" D (11.4cm)	1800°F (982°C)	.167 (4.7L)	120V	12A	1440W	NEMA 5-15R	30 lb. (14kg)
							230V	9.6A	2208W	NEMA 6-20R	
Studio 8	No	8" (20.3cm)	8" (20.3cm)	4.5" D (11.4cm)	1800°F (982°C)	.167 (4.7L)	120V	12A	1440W	NEMA 5-15R	30 lb. (14kg)
							230V	9.6A	2208W	NEMA 6-20R	
Studio Pro 14	Yes	14.5" (36.8cm)	14.5" (36.8cm)	6.5" D (16.5cm)	1650°F (899°C)	.800 (22.7L)	120V	15A	1800W	NEMA 5-15R	130 lb. (55kg)
							240V	10A	2400W	NEMA 6-20R	
V8	No	8" (20.3cm)	8" (20.3cm)	6.5" D (16.5cm)	2350°F (1260°C)	.240 (6.8L)	120V	14A	1680W	NEMA 5-15R	45 lb. (22kg)
							240V	10A	2400W	NEMA 6-20R	
Studio Pro 15	Yes	14.5" (36.8cm)	14.5" (36.8cm)	6.5" D (16.5cm)	1650°F (899°C)	.800 (22.7L)	120V	15A	1800W	NEMA 5-15R	130 lb. (55kg)
							240V	10A	2400W	NEMA 6-20R	
Studio Pro 17	Yes	17" (43.2cm)	17" (43.2cm)	6.5" D (16.5cm)	1650°F (899°C)	1.09 (30.9L)	120V	18A	2160W	NEMA 5-20R	135 lb. (61kg)
							240V	10A	2400W	NEMA 6-20R	
Studio Pro 24	Yes	24" (61cm)	24" (61cm)	13.5" D (34.3cm)	1800°F (982°C)	4.20 (119L)	240V	32A	7680W	NEMA 6-50R	280 lb. (127kg)
							208V	37A	7700W	NEMA 6-50R	
							400V	10.5A	7015W	Varies	
Studio Pro 28	No	28" (71cm)	28" (71cm)	13.5" D (34.3cm)	1800°F (982°C)	5.82 (165L)	240V	40A	9600W	NEMA 6-50R	300 lb. (136kg)
							208V	46A	9568W	NEMA 6-50R	
							400V	38.3A	8809	Varies	
Studio Pro 41	Yes	40.5" (102.9cm)	25.25" (64.1CM)	13.5" D (34.3CM)	1800°F (982°C)	7.52 (213L)	240V	45A	10800W	NEMA 6-50R	365 lb. (166kg)
							208V	48A	9984W	NEMA 6-50R	
							400V	17A	10,071W	Varies	
TGK GT 4050	No	19.75"	15.75"	6.5" D	1650°F	1.20	240V	15A	3600W	NEMA 6-20R	135 lb.

Specifications subject to change without notice or obligation. Model features and options may affect TUV listing.
Standard production models are 240V, single phase. 208V and 3 Phase designs are available.
Evenheat offers kilns designed for 380/400/415V as well as kilns designed for Europe bearing the CE mark.