

Ceramic Kiln Specifications – North America

Model	TUV Listed U.S. & Canada	Chamber Diameter	Chamber Length	Chamber Depth	Maximum Usable Temperature	Cubic Feet	Volts	Amps	Watts	Power Receptacle	Ship Weight
Evolution 2318	Yes	23"	23"	18"	2300°F	5.2	240V 208V	37A 43A	8880W 8944W	NEMA 6-50R	270 lb.
Evolution 2327	Yes	23"	23"	27"	2300°F	7.8	240V 208V	48A 48A	11,520W 9984W	NEMA 6-50R	310 lb.
HF 810	Yes	11.25"		9"	2250°F	.57	240V	18A	2160W	NEMA 5-20R	75 lb.
HF 1210B	Yes	11.25"		13.5"	2350°F	.86	240V	13A	3120W	NEMA 6-20R	85 lb.
HF 1413	Yes	14.5"		13.5"	2350°F	1.3	240V	15A	3600W	NEMA 6-20R	130 lb.
HF 1813	Yes	17.5"		13.5"	2350°F	2.0	240V 208V	21A 24A	5040W 4992W	NEMA 6-30R	150 lb.
HF 1818	Yes	17.5"		18"	2350°F	2.7	240V 208V	28A 27A	6672W 5616W	NEMA 6-30R	180 lb.
HF 2318	Yes	23.5"		18"	2350°F	4.7	240V 208V	31A 31A	7440W 6448W	NEMA 6-50R	240 lb.
HF 2327	Yes	23.5"		27"	2350°F	7.0	240V 208V	48A 48A	11,520W 9984W	NEMA 6-50R	330 lb.
HF 2918	Yes	29"		18"	2350°F	7.0	240V 208V	48A 48A	11,520W 9984W	NEMA 6-50R	350 lb.
HF 2927	Yes	29"		27"	2350°F	10.5	240V 208V	59A 69A	14,164W 14,400W	Direct	430 lb.
RM2 810	Yes	11.25"		9"	2200°F	.57	120V	18A	2160W	NEMA 5-20R	62 lb.
RM2 1210	Yes	11.25"		13.5"	1800°F	.86	120V	19A	2280W	NEMA 5-20R	70 lb.
RM2 1210B	Yes	11.25"		13.5"	2300°F	.86	240V	13A	3120W	NEMA 6-20R	70 lb.
RM2 1413	Yes	14.5"		13.5"	2300°F	1.3	240V	15A	3600W	NEMA 6-20R	100 lb.
RM2 1813	Yes	17.5"		13.5"	2300°F	2.0	240V	18A	4320W	NEMA 6-30R	115 lb.
RM2 1822	Yes	17.5"		22.25"	2300°F	3.3	240V	30A	7200W	NEMA 6-50R	145 lb.
RM2 2322	Yes	23.5"		22.25"	2300°F	5.8	240V	39A	9240W	NEMA 6-50R	215 lb.
RM2 2329	Yes	23.5"		29"	2300°F	7.5	240V	45A	10,800W	NEMA 6-50R	240 lb.
RM2 2922	Yes	29"		22.25"	2300°F	8.7	240V	44A	10,560W	NEMA 6-50R	250 lb.
RM2 2929	Yes	29"		29"	2300°F	11.3	240V	56A	13,440W	Direct	290 lb.
RM2 2522	Yes	41"	25.25"	22.25"	2000°F	11.2	240V	47A	11,280W	NEMA 6-50R	410 lb.
RM2 2541	Yes	41"	25.25"	29"	2000°F	14.4	240V	60A	14,400W	Direct	450 lb.
Copper	Yes	10"	6.5"	9"	2200°F	.340	120V	12A	1440W	NEMA 5-20R	54 lb.
V8	No	8"	8"	6.5"	2350°	.24	120V	14A	1680W	NEMA 5-15R	45 lb.
810	No	11.25"		9"	2200°F	.57	120V	18A	2160W	NEMA 5-20R	62 lb.
1210	No	11.25"		13.5"	1800°F	.86	120V	19A	2280W	NEMA 5-20R	70 lb.
1210B	Yes	11.25"		13.5"	2300°F	.86	240V	13A	3120W	NEMA 6-20R	70 lb.
1413	Yes	14.5"		13.25"	2300°F	1.3	240V	15A	3600W	NEMA 6-20R	100 lb.
3220	Yes	17.5"		13.5"	2300°F	2.0	240V	18A	4320W	NEMA 6-30R	115 lb.
4320	Yes	17.5"		18"	2300°F	2.6	240V	24A	5760W	NEMA 6-30R	130 lb.

Specifications subject to change without notice or obligation. Model features and options may affect TUV listing.
Standard production models are 240V, single phase. 208V and 3 Phase designs are available.
Evenheat offers kilns designed for 380/400/415V as well as kilns designed for Europe bearing the CE mark.

Ceramic Kiln Specifications – North America

Model	TUV Listed U.S. & Canada	Chamber Diameter	Chamber Length	Chamber Depth	Maximum Usable Temperature	Cubic Feet	Volts	Amps	Watts	Power Receptacle	Ship Weight
1822-S	Yes	17.25"		22.5"	2300°F	3.3	240V	30A	7200W	NEMA 6-50R	145 lb.
4320XL	Yes	23.5"		18"	2300°F	4.7	240V	30A	7200W	NEMA 6-50R	200 lb.
5320XL	Yes	23.5"		22.5"	2300°F	5.8	240V	38A	9000W	NEMA 6-50R	215 lb.
6320XL	Yes	23.5"		27"	2300°F	7.0	240V	45A	10,800W	NEMA 6-50R	230 lb.
2918	Yes	29"		18"	2300°F	7.0	240V	37A	8880W	NEMA 6-50R	260 lb.

Specifications subject to change without notice or obligation. Model features and options may affect TUV listing.
Standard production models are 240V, single phase. 208V and 3 Phase designs are available.
Evenheat offers kilns designed for 380/400/415V as well as kilns designed for Europe bearing the CE mark.